

# SILIKON M MATERIAL DATA SHEET

## TECHNICAL DATA SHEET

Type: Cellular Rubber  
Quality: EPDM  
Colour: Grey

		Typical value	Method
Density	kg/m <sup>3</sup>	+/- 210	ISO-845-88
Compression deflection''''''''72'	kPa	+/-100	D421541
Compression set 40°C	%	≤ 25%	D411540
Temperature range	°C	Intermittent	-
		Continuous	-50°C/120°C
Flammability rating	HL2 for R22/R23/R24		EN 45 545-:2013
	M2F1		NF F16101
Typical resistance	Oil	NA	
	Ozone	No cracks	
	Air+UV	Very good	
Features	Excellent fire and smoke retardant cellular rubber for inside and outside applications.		

The data and information provided here-above represent typical data and are intended to provide information on our products and their possible applications. Those data are not specifications and do not guarantee the suitability of the product for a given application. Therefore we recommend the end-user to determine the suitability of the product for the specific application it is intended for.

January 2017



SILIKON M Magdalena Dikelman  
ul. Wiosenna 53, 57-300 Kłodzko, Poland  
tel: +48 502 742 056  
e-mail: [biuro@silikony.ng.pl](mailto:biuro@silikony.ng.pl)  
internet: [www.silikony.ng.pl](http://www.silikony.ng.pl)